

## **HOMEHEAT SERIES SPECIFICATIONS**



| MODEL                               | H300  | H450       | H600       | H800       |
|-------------------------------------|---|------------|------------|------------|
| MSRP                                | \$940.00  | \$1,000.00 | \$1,050.00 | \$1,120.00 |
| PACKAGE CONTENTS                    | Heater, Built-in Controls, Sensor, Sensor Cover, Sensor Wood Molding, Rocks, Caution Sign, Warning Sign |            |            |            |
| HEATER INFORMATION                  |   |            |            |            |
| PLACEMENT                           | Wall-Mounted  |            |            |            |
| DIMENSIONS (L x D X H)              | 16" x 11" x 24"   |            |            |            |
| MATERIALS OF CONSTRUCTION           | Stainless   |            |            |            |
| WEIGHT                              | 34lbs   |            |            |            |
| ROCK WEIGHT                         | 45lbs   |            |            |            |
| OPERATING WEIGHT (W/ ROCKS)         | 75lbs   |            |            |            |
| HEATER RANGES                       |   |            |            |            |
| ROOM SIZE RANGE (CUBIC FEET)        | 84-130  | 100-210    | 170-300    | 250-425    |
| ROOM SIZE RANGE (SQUARE FEET)       | 10-20   | 16-30      | 28-40      | 40-65      |
| MAX ROOM HEIGHT (FEET)              | 8'  |            |            |            |
| HEATER ELECTRICAL DATA              |   |            |            |            |
| KILOWATT                            | 3kW   | 4.5kW      | 6kW        | 8kW        |
| VOLTAGE                             | 240V  | 240V       | 240V       | 240V       |
| PHASE                               | 1PH   | 1PH        | 1PH        | 1PH        |
| AMPS                                | 12.5 Amps   | 18.8 Amps  | 25 Amps    | 33.3 Amps  |
| CONTROL SYSTEM (included)           |   |            |            |            |
| CONTROL                             | Built-In  |            |            |            |
| LOCATION                            | Lower Right Front Corner; Can Be Relocated To Either Side Near Bottom                                   |            |            |            |
| STYLE                               | Dial  |            |            |            |
| FEATURES                            | Time/Temp, Start Delay  |            |            |            |
| TIME DURATION                       | Up to 60 Minutes  |            |            |            |
| TEMPERATURE RANGE                   | 104 Deg F TO 194 Deg F  |            |            |            |
| DELAY START TIME                    | Up to 8 hours settable in 1-hr increments   |            |            |            |
| SENSOR CABLE LENGTH                 | 8' Included   |            |            |            |
| SAFETY                              |   |            |            |            |
| SAFETY RATINGS / CERTIFICATIONS     | UL LISTED   |            |            |            |
| SHIPPING                            |   |            |            |            |
| HEATER BOX SIZE (L x D x H), WEIGHT | 19.5" x 14.75" x 28.5", 35lbs   |            |            |            |
| ROCKS BOX SIZE (L x D x H), WEIGHT  | 15" x 11" x 5.5", 45lbs   |            |            |            |
| WARRANTY                            |   |            |            |            |
| PARTS WARRANTY                      | Limited Lifetime Parts  |            |            |            |
| LABOR WARRANTY                      | Limited Lifetime Labor  |            |            |            |